Job Name/Location: Tag No.:

Date:	For: File Resubmit
PO No.:	Approval Other
Architect:	GC:
Engr:	Mech:

Rep:
(Company) (Project Manager)

PREM TA201

LG Deluxe Wired Remote Controller

Controller w/Built-in Wi-Fi & LG ThinQ®Compatability



Power Supply 12VDC Power From Indoor Unit

Operating Environment:

Operating Temperature	32°F ~104°F (0°C ~ 40°C)
Storage Temperature	-4°F ~ +140°F (-20°C ~ +60°C)
Humidity Operating Temperature	0 ~ 90 % (RH)
Humidity Storage Temperature	0 ~ 90 % (RH)

Unit Data:

Dimensions	4.72" H x 4.72" W x 0.59"	D
Maximum Number of Indoor Units (per cor	ntroller)	16
Maximum Number of Controllers (per grou	p)	1


Features:1

- Wi-Fi with ThinQ Capability
- Function Code Settings
- Function Code Search Tool
- Date and Time Display
- Room Temperature Display
- Humidity Display
- Operation On / Off
- Modes Auto / Cool / Dry / Heat / Fan Only
- Cooling and Heating Temperature Setpoints
- Energy Management
- Installation Wizard Commercial / Residential Applications
- Proximity Sensor
- Al Smart Care
- Fan Speeds Auto / Low / Med / High / Power
- ERV Compatibility
- Static Pressure Installer Setting

Optional Accessories:

☐ PZCWRC1 - 33-foot Extension Cable Assembly

☐ PZCWRCG3 - Group Control Cable Kit







Connectivity:


LG Communications	1 Channel for V-Net,
	Wi-Fi with ThinQ Capability

Communications Cable Specifications (V-Net):

Туре	Three (3) Conductor, Stranded, Twisted, Unshielded
Size	AWG 22-3
Length ²	Up to 164 feet

AWG - American Wire Gauge

Controller Wiring:



GND / SIG / 12V

Notes:

- 1. Available functions / features may differ based on connected system.
- Communication cable can be extended to a maximum of 164 feet by using field-supplied wire or the Wired Remote Group Control Cable Assembly (PZCWRCG3) or Wired Remote Extension Cable (PZWRC1), maximum of four (4).
- Must follow installation instructions in the applicable LG installation manual.